



Configuration Table					
Part Number	Closed Length "L"	Stroke Length "C"	Load Per Pair (kg)	Drill Table	
				Pitch	Qty
4013.8045.0300	300	170	350	120	3
4013.8045.0350	350	270	355	145	3
4013.8045.0400	400	370	360	170	3
4013.8045.0450	450	470	370	195	3
4013.8045.0500	500	570	380	110	5
4013.8045.0550	550	550	390	122.5	5
4013.8045.0600	600	650	400	135	5
4013.8045.0650	650	750	390	118	6
4013.8045.0700	700	700	380	128	6
4013.8045.0750	750	750	370	138	6
4013.8045.0800	800	800	355	148	6
4013.8045.0850	850	800	340	158	6
4013.8045.0900	900	900	325	168	6
4013.8045.0950	950	1000	315	178	6
4013.8045.1000	1000	1100	300	188	6

Mounting details
Refer to drill table hole pitches



We recommend use the major axis, do not dismantle the slide! The maximum safe load is given for a fully extended pair of slides, mounted on the major axis, with a load spread uniformly along the inner beam.

- Beams: Aluminium grade 6005a milled for accuracy. Clear anodised as standard
- Rollers: Chromed steel. Cross rollers for rigidity
- Cages: Plated steel. Laser cut for accuracy
- High impact shock spring stops
- Lubrication: Berulub FR 16 B. (Range: -50 – 140 °C) High temp on request
- Standard lengths & extensions from 300 – 1000mm
- Special lengths, drillings & black surface finish subject to MOQ
- Operating temperatures between -40 – +200 °C (with nylon parts removed)
- All steel components without spring stops for value production subject to MOQ

RADIAL RANGE: Telescopic