

OWS-48 weighs 3.38kg/m. Sold as singles

Part Number	Closed Length: L	Extension Length: D	Load per Pair: kg	Drilling Pattern		
				"A"	"B"	"C"
4015.OWS048.0150	150	75	80	50	-	-
4015.OWS048.0200	200	100	90	50	-	-
4015.OWS048.0250	250	125	110	50	-	50
4015.OWS048.0300	300	150	130	50	-	100
4015.OWS048.0350	350	175	150	50	-	150
4015.OWS048.0400	400	200	180	50	-	200
4015.OWS048.0450	450	225	240	50	-	250
4015.OWS048.0500	500	250	260	50	-	300
4015.OWS048.0550	550	275	280	50	150	-
4015.OWS048.0600	600	300	270	50	175	-
4015.OWS048.0650	650	325	260	50	200	-
4015.OWS048.0700	700	350	250	50	225	-
4015.OWS048.0750	750	375	240	50	250	-
4015.OWS048.0800	800	400	230	50	275	-
4015.OWS048.0850	850	425	220	50	300	-
4015.OWS048.0900	900	450	210	50	325	-
4015.OWS048.0950	950	475	200	50	350	-
4015.OWS048.1000	1000	500	190	50	375	-
4015.OWS048.1050	1050	525	170	50	400	-
4015.OWS048.1100	1100	550	150	50	425	-
4015.OWS048.1150	1150	575	130	50	450	-
4015.OWS048.1200	1200	600	110	50	475	-

Professional Range - **Steel**
Partial Extension Telescopic Slide

OWS-48

SLIDING
SYSTEMS

Type: OWS-48

Version: 2021/1



If mounting on the indirect axis, flat, as in the image above, reduce the load capacity by 60-80% and allow for increased deflection, or contact our engineers to request accurate FEA load analysis for OEM projects. We load rate per fully extended pair of slides on the direct axis, upright, with uniform loading across the beams. If load capacities need to be increased, please contact us for technical advice.

Material: All steel parts/no plastics

Beams: Cold drawn carbon steel C45E+C. EN 10277 milled raceways

Ball bearings: Chromed steel C85, G100. Din 5401

Ball cages: Zinc plated sheet steel. Laser cut profiles

End bolts: Steel ASTM A307

Surface Protection: Electrolytic alkaline zinc coating (10-12 microns). conforming to DIN EN ISO 9227 neutral salt spray testing. No white rust appearance within 120 hours. No red rust within 1,032 hours

Temperature range: Steel slides -20°C to +250°C provided the necessary lubricants are applied and the beams are mounted freely to allow expansion

Lubrication: We apply and recommend lithium based EP3 grease for general applications.

High & low temp grease upon request

Thread pitches: As per end profile image - coarse

Options:

'F' - One mounting beam countersunk

'FF' - Both beams countersunk

'SB' - Stainless steel 316L ball bearings


'SC' - Stainless steel ball cages

'SA' - Stainless end bolts & retaining pins

'V' - V shaped raceways (bi-directional slides)

'70' - 70% over-extension of standard slide

Bespoke length, drilling pattern & extension on request

Do not dismantle the slide! 
The maximum safe working load is stated for a fully extended pair of slides, mounted upright. Use all fixing holes and spread the load evenly across the inner beam.

Flat mounting: Reduce the load by 60-80%. We recommend the use of strong L brackets for under or floor mount.

Deflection is calculated at approx 1% of the closed length, at or near full load capacity.



'Global Company, Global Reach'